

BASIC

COLOURED BODY PORCELAIN

SIZES - CEMENT VISUAL

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	24 x 48 Field Tile (Unpolished)	(23-3/8" x 46-7/8") (59.50 cm x 119.20 cm)	3/8"	15.50	2
	24 x 24 Field Tile (Unpolished & Textured*)	(23-3/8" x 23-3/8") (59.50 cm x 59.50 cm)	3/8"	11.64	3
	12 x 24 Field Tile (Unpolished & Textured)	(11-5/8" x 23-3/8") (29.65 cm x 59.50 cm)	3/8"	9.70	5

* 24 x 24 textured field tile is available via special order. Contact your local sales representative for more information.

SIZES - FABRIC VISUAL

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	24 x 24 Field Tile (Unpolished)	(23-3/8" x 23-3/8") (59.50 cm x 59.50 cm)	3/8"	11.64	3
	12 x 24 Field Tile (Unpolished)	(11-5/8" x 23-3/8") (29.65 cm x 59.50 cm)	3/8"	9.70	5

FLOOR APPLICATIONS - CEMENT VISUAL

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	✓*
Ramps & Inclines	≥ 0.65	✓*




* Textured surface only

FLOOR APPLICATIONS - FABRIC VISUAL

	Target DCOF wet	Suitable
Dry & Level – Interior	N/A	✓
Wet & Level – Interior	≥ 0.42	✓
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	


A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

TRIM

Type	Number	Size	Pieces per Carton
 Bullnose	S-43C9	3 x 12	30
 Cove Base	S-36C9T	6 x 12	20
 Cove Base Outcorner	SC-36C9T	1 x 6	10

Floor bullnose, cove base, and cove base corner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and when installed in a staggered brick-joint pattern; overlap should not exceed 33%)	 High (V3)

TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 450 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

NOTES

Special consideration needs to be given when installing tiles greater than 15". Please refer to daltile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and not from tile samples or color reproductions. Manufactured in accordance with ANSI A1371 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.

